



Clothes Dryer Transition Duct



Product Specifications

A Clothes Dryer Transition Duct offers the most flexibility in the laundry room by allowing the dryer to be situated closely to the wall. When properly installed to an exhaust duct, it will provide safe and proper airflow, leading to faster drying times. Quietflex Clothes Dryer Transition Duct can be used on both electric and gas dryers.

www.quietflex.com

Key Features & Benefits

- Easy to install boxed universal flexible dryer duct
- Fire resistant, heavy duty 4-ply aluminum foil laminate construction
- Fits most commonly used electric and gas dryers
- Fits in tight places where rigid metal ducting will not work
- Close wire frame spacing allows tight bends without collapsing
- Meets all the requirements of UL 2158A

Other products we offer:

- 5', 6' & 7' Collared Silver Jacket Flex
- Uninsulated Flex Connector





FLEX DUCT PRODUCT:

CLOTHES DRYER TRANSITION DUCT

Performance Data as Required by UL 2158A

- Proven Corrosion Resistant Construction
- Flame Spread as Per UL 723 Testing of Less than 25
- Complies with Stringent Fire Resistance Testing
- Stands Up to Repeated Bending
- Undamaged as a Result of Specified Impacts
- Strong in Tension
- Resists Damage Caused by Twisting



Product Specifications

DIAMETERS	BOXED LENGTHS
Inch	Ft
Nominal 4" (actual 4.125)	8
Each hose will be packaged individually and then placed in a master carton. 57 pcs for 8', 25 pcs for 25', and 10 pcs for 50'	8
	25
	50

Note: Boxed products sold above 8 feet in length are never allowed to display the UL listing.

Job Name		Submitter:		Date:	
Location					Class 1 Dryer Transition Duct
Contractor					
Engineer					
Architect					
					QFSD-008-01

4518 Brittmoore Road • Houston, Texas 77041 • Phone 713.849.2163 • quietflex.com

Limited Warranty | Limitation of Liability | Disclaimer of Unstated Warranties
 The flexible air duct is warranted by Quietflex Manufacturing Company, L.P., for ten (10) years against defects in material and workmanship. This warranty is for exchange of duct only and does not include installation.

Warranty Exclusions
 Warranty is excluded if flexible air duct is used in the following installations / applications:
 1. Where duct is exposed to direct or indirect light.
 2. Where duct is used on the high – pressure side of variable air – volume (VAV) systems.

Limitation of Liability
 Quietflex's liability for damages, whether in contract, in tort, under warranty, in negligence or otherwise, shall not exceed the return of the amount of the purchase price paid for the Quietflex products. Quietflex shall not be liable for special, indirect or consequential damages. Specification and performance data listed herein are subject to change without notice.

Disclaimer of Unstated Warranties
 This warranty is the only warranty of Quietflex products. All other warranties, expressed or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose are expressly disclaimed. Quietflex is a registered trademark of Quietflex Manufacturing Company, L.P.